

# TEXTURE BLEND

## **MIXING INSTRUCTIONS:**

Machine or drill mix using paddle mixer. 40 Lbs. of Texture Blend to 3-4 quarts (depending on desired texture) of premixed PermaPro Acrylo Bond admix (1 to 1 with water). Add PermaPro EZ Color Pak, if desired, at this point and mix thoroughly again. ONLY mix up what can be applied within the next 30 minutes based on 70°F weather.

## **HOW TO USE:**

Troweled 1/8 inch to 1/4 inch thick using a pool trowel or squeegee trowel, textured while wet and applicable, and then knocked down with the pool trowel once material has stiffened but not dried.

## **PRECAUTIONARY STATEMENT:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

## **FIRST AID:**

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconscious person.

## **IN CASE OF FIRE:**

This product is not flammable.

## **FOR EMERGENCY HELP**

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053